

Avionics

PSD30-2AF Universal DC Capacitance Test Set

NSN: 6625-01-416-7180

AEROFLEX
A passion for performance.




The PSD30-2AF is designed to calibrate and troubleshoot any DC capacitive fuel quantity system. The PSD30-2AF will perform the following functions:

- Measure the capacitance or insulation resistance of any DC capacitive fuel quantity system with required aircraft specific interface cable (not included).
- Simulate the capacitance of any DC fuel quantity system to calibrate or troubleshoot the system.
- Measure the DC voltage to the fuel quantity gauge in the range of 0-40 VDC in .01 VDC increments.

FEATURES

- Solid-state circuits and Liquid Crystal Display for low power consumption and high reliability. LCD is backlit for enhanced viewing.
- Tested and approved for use with fuel in tanks.
- Portable, lightweight, sealed, high-impact ABS case reduces weight of tester with batteries installed to less than 12 pounds.
- Small size permits testing in restricted spaces - 10.5"W x 14"L x 6"H. Ideal for Forward Area Deployment.
- Very easy to operate. Choose the FUNCTION desired and read the measured capacitance, insulation or voltage on the display.

- Auto-ranging circuit and 4.5 digit display permit resolution to .01 pF in capacitance functions and .01 meg in insulation (megger) function.
- Digital Multi-meter (DMM) function reads external voltage up to 40 VDC.
- BATTERY CHECK function reads % of usable battery charge remaining.
- Recommended annual calibration interval. Stability of the measuring circuit eliminates need to recalibrate each time unit is used.
- Two year standard warranty.
- CE Marked - 

SPECIFICATIONS

CAPACITANCE SIMULATION AND MEASUREMENT

Ranges

Lo - 0 to 199.99 pF in .01 pF increments

Hi - 200 to 1999.9 pF in .1 pF increments

Accuracy

±.1% of reading or .1 pF, whichever is greater (-20° C to +50° C)

RESISTANCE MEASUREMENT

Range

100 KΩ to 2,000 MΩ

Accuracy

±10% of reading from 0° C to +50° C or

±15% of reading from -20° C to 0° C

For the very latest specifications visit www.aeroflex.com

DIGITAL VOLTMETER MEASUREMENT

Range

0 to 40 VDC in .01 volt increments

Accuracy

±.5% of full scale (.2 VDC)

POWER REQUIREMENTS

Input

18 C cell batteries

PHYSICAL CHARACTERISTICS

Size

10.5" X 14" X 6.5"

(26.7 cm X 35.6 cm X 16.5 cm)

Weight

12 lbs. (5.4 Kg)

SUPPLEMENTAL INFORMATION

Test Set Certifications

Safety Compliance EN 61010-1

EMC EN 61326

ORDERING INFORMATION

PSD30-2AF Universal DC Capacitance Test Set
(NSN: 6625-01-416-7180)

EXTENDED WARRANTY

WPSD/203C Extended standard warranty 36 months with scheduled calibration

WPSD/205C Extended standard warranty 60 months with scheduled calibration

Aircraft specific interface cables are required and must be purchased separately. Contact Aeroflex for your application.

CHINA Beijing
Tel: [+86] (10) 6467 2761 2716
Fax: [+86] (10) 6467 2821

CHINA Shanghai
Tel: [+86] (21) 6282 8001
Fax: [+86] (21) 62828 8002

FINLAND
Tel: [+358] (9) 2709 5541
Fax: [+358] (9) 804 2441

FRANCE
Tel: [+33] 1 60 79 96 00
Fax: [+33] 1 60 77 69 22

GERMANY
Tel: [+49] 8131 2926-0
Fax: [+49] 8131 2926-130

HONG KONG
Tel: [+852] 2832 7988
Fax: [+852] 2834 5364

INDIA
Tel: [+91] 80 5115 4501
Fax: [+91] 80 5115 4502

KOREA
Tel: [+82] (2) 3424 2719
Fax: [+82] (2) 3424 8620

SCANDINAVIA
Tel: [+45] 9614 0045
Fax: [+45] 9614 0047

SPAIN
Tel: [+34] (91) 640 11 34
Fax: [+34] (91) 640 06 40

UK Burnham
Tel: [+44] (0) 1628 604455
Fax: [+44] (0) 1628 662017

UK Stevenage
Tel: [+44] (0) 1438 742200
Fax: [+44] (0) 1438 727601
Freephone: 0800 282388

USA Wichita
Tel: [+1] (316) 522 4981
Fax: [+1] (316) 522 1360
Toll Free: 800 835 2352

USA New Century
Tel: [+1] (913) 764 2452
Fax: [+1] (913) 782 5104

As we are always seeking to improve our products, the information in this document gives only a general indication of the product capacity, performance and suitability, none of which shall form part of any contract. We reserve the right to make design changes without notice. All trademarks are acknowledged. Parent company Aeroflex, Inc. ©Aeroflex 2006.

www.aeroflex.com
info-test@eroflex.com



Our passion for performance is defined by three attributes represented by these three icons: solution-minded, performance-driven and customer-focused.